

Product **male angled cable connector, overmoulded, stainless steel, PVC cable**
 Area **M12-A Series 763 FOOD & BEVERAGE**
 Article number **77 3727 0000 20912-0200**

Illustration	Scale drawing	Contact Arrangement																																							
		<table border="1" style="margin: 10px auto;"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> </tr> </thead> <tbody> <tr><td>1</td><td>2,80</td><td>0,78</td></tr> <tr><td>2</td><td>0,78</td><td>2,80</td></tr> <tr><td>3</td><td>-1,09</td><td>2,69</td></tr> <tr><td>4</td><td>-2,51</td><td>1,46</td></tr> <tr><td>5</td><td>-2,88</td><td>-0,37</td></tr> <tr><td>6</td><td>-2,05</td><td>-2,05</td></tr> <tr><td>7</td><td>-0,37</td><td>-2,88</td></tr> <tr><td>8</td><td>1,46</td><td>-2,51</td></tr> <tr><td>9</td><td>2,69</td><td>-1,09</td></tr> <tr><td>10</td><td>0,78</td><td>0,78</td></tr> <tr><td>11</td><td>-1,06</td><td>0,29</td></tr> <tr><td>12</td><td>0,29</td><td>-1,06</td></tr> </tbody> </table> <p style="font-size: small; text-align: center;">Geschirmte Versionen: Schirm auf Gehäuse Shielded versions: shield on housing</p>		X	Y	1	2,80	0,78	2	0,78	2,80	3	-1,09	2,69	4	-2,51	1,46	5	-2,88	-0,37	6	-2,05	-2,05	7	-0,37	-2,88	8	1,46	-2,51	9	2,69	-1,09	10	0,78	0,78	11	-1,06	0,29	12	0,29	-1,06
	X	Y																																							
1	2,80	0,78																																							
2	0,78	2,80																																							
3	-1,09	2,69																																							
4	-2,51	1,46																																							
5	-2,88	-0,37																																							
6	-2,05	-2,05																																							
7	-0,37	-2,88																																							
8	1,46	-2,51																																							
9	2,69	-1,09																																							
10	0,78	0,78																																							
11	-1,06	0,29																																							
12	0,29	-1,06																																							

Technical data

General features

Connector Design	Cable Connector
Connector locking system	screw
Termination	crimp, overmoulded on cable
Wire gauge (mm)	0,25
Wire gauge (AWG)	24
Upper temperature	105 °C
Lower temperature	-40 °C

Cable data

material housing	PVC
Insulation single lead	PVC
Single lead structure	32 x 0,1
Cable sheath Ø	6,6
Conductor resistance	75 Ω/Km (20°C)
Temperature range cable movable °C from	-5
Temperature range cable movable °C to	105
Temperature range cable fixed °C from	-40
Temperature range cable fixed °C to	105
Bending radius cable fixed	min. 5 x D
Bending radius cable movable	min. 10 x D
Approval 1	UL listed
Approval 2	Ecolab

Electrical parameters

Rated voltage	30 V
Rated impulse voltage	800 V
Pollution degree	3
Overvoltage category	II
Material group	II
Rated current (40°C)	1,5 A
Volume resistivity	≤ 3 mΩ
EMV compliance	not shielded
Degree of protection	IP69K
Mechanical operation	> 100 Mating cycles

Material

Material of contact	CuSn (Bronze)
Contact plating	Au (gold)
Material of contact body	PP
Material of housing	PP