

Product sheet

Output connector



Product	Contacts: 9, Female panel mount connector, front mounting (the pin and socket insert counter-rotate in right and left turning models)	Area	M23 Power Series 623
Pole	9	Article number	99 4604 10 09

Illustration	Scale drawing	Contact Arrangement																														
		<table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> </tr> </thead> <tbody> <tr><td>1</td><td>1,80</td><td>4,35</td></tr> <tr><td>2</td><td>4,35</td><td>1,80</td></tr> <tr><td>3</td><td>4,35</td><td>-1,80</td></tr> <tr><td>4</td><td>1,80</td><td>-4,35</td></tr> <tr><td>5</td><td>-1,80</td><td>-4,35</td></tr> <tr><td>6</td><td>-4,35</td><td>-1,80</td></tr> <tr><td>7</td><td>-4,35</td><td>1,80</td></tr> <tr><td>8</td><td>-1,80</td><td>4,35</td></tr> <tr><td>9</td><td>0,00</td><td>0,00</td></tr> </tbody> </table>		X	Y	1	1,80	4,35	2	4,35	1,80	3	4,35	-1,80	4	1,80	-4,35	5	-1,80	-4,35	6	-4,35	-1,80	7	-4,35	1,80	8	-1,80	4,35	9	0,00	0,00
	X	Y																														
1	1,80	4,35																														
2	4,35	1,80																														
3	4,35	-1,80																														
4	1,80	-4,35																														
5	-1,80	-4,35																														
6	-4,35	-1,80																														
7	-4,35	1,80																														
8	-1,80	4,35																														
9	0,00	0,00																														

Technical data

Common values

Connector Design	Female panel mount connector
Connector locking system	screw
Termination	Solder
Wire gauge (mm)	8x1.5/ 1x2.5 mm ²
Wire gauge (AWG)	8x16/ 1x14
Cable outlet	-
Upper temperature	125 °C
Lower temperature	-20 °C

Electrical values

Rated voltage	300 V
Rated impulse voltage	2500 V
Pollution degree	3
Overvoltage category	II
Material group	III
Rated current (40°C)	8x8A/ 1x20A
Volume resistivity	≤ 3 mΩ
EMV compliance	not shielded
Degree of protection	IP67
Mechanical operation	> 50 mating cycles

Material

Material of contact	CuSn (Bronze)
Contact plating	Au (Gold)
Material of contact body	PBT/PA66
Material of housing	Nickel-plated zinc die casting

Contacts: 9, Female panel mount connector, front mounting, left-turning