

Product	Contacts 3: Cable plug connector M12x1 - female angled connector, with LED PNP NOC (normally open contact) M12x1, 3x0.34 PUR	Area	Connecting cords Series 765
Pole	3	Article number	79 5003 20 04

Illustration	Scale drawing	Contact Arrangement
		<p> Stifteinsatz M12 Male insert M12 </p> <p> Buchseinsatz M12 Female insert M12 </p> <p> 1 braun/brown 3 blau/blue 4 schwarz/black </p>

Technical data

Common values

Connector Design	Cable plug connector - female angled connector
Connector locking system	screw
Termination	crimp, injection-moulded cable
Wire gauge (mm)	0.34 mm ²
Wire gauge (AWG)	22
Upper temperature	85 °C
Lower temperature	-25 °C

Electrical values

Rated voltage	30 V
Rated impulse voltage	500 V
Pollution degree	3
Overvoltage category	II
Material group	II
Rated current (40°C)	4 A
Volume resistivity	≤ 3 mΩ
EMV compliance	nicht geschirmt
Degree of protection	IP68
Mechanical operation	> 100 mating cycles

Material

Material of contact	Pin/ CuZn (brass), socket/ CuSn (bronze)
Contact plating	Au (Gold)
Material of contact body	PUR
Material of housing	PUR

Contacts 3: Connecting cord 2 m, cable plug connector M12 x 1 - female angled connector with LED PNP NOC (normally open contact) M12 x 1, cable 3 x 0.34 PUR