

Product sheet

Subminiature connector



Product	Contacts: 7, Female cable connector, 360° EMC safe, cable outlet 3.5-5 mm	Area	M9 IP67 Series 712
Pole	7	Article number	99 0422 10 07

Illustration	Scale drawing	Contact Arrangement																								
		<table border="1"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>-0,90</td> <td>-1,65</td> </tr> <tr> <td>2</td> <td>-1,85</td> <td>-0,35</td> </tr> <tr> <td>3</td> <td>-1,45</td> <td>1,20</td> </tr> <tr> <td>4</td> <td>0,00</td> <td>1,85</td> </tr> <tr> <td>5</td> <td>1,45</td> <td>1,20</td> </tr> <tr> <td>6</td> <td>1,85</td> <td>-0,35</td> </tr> <tr> <td>7</td> <td>0,90</td> <td>-1,65</td> </tr> </tbody> </table>		X	Y	1	-0,90	-1,65	2	-1,85	-0,35	3	-1,45	1,20	4	0,00	1,85	5	1,45	1,20	6	1,85	-0,35	7	0,90	-1,65
	X	Y																								
1	-0,90	-1,65																								
2	-1,85	-0,35																								
3	-1,45	1,20																								
4	0,00	1,85																								
5	1,45	1,20																								
6	1,85	-0,35																								
7	0,90	-1,65																								

You can find the item description on the next page.

Technical data

Common values

Connector Design	Female cable connector
Connector locking system	screw
Termination	Solder
Wire gauge (mm)	0.14 mm ²
Wire gauge (AWG)	26
Cable outlet	3.5 - 5 mm
Upper temperature	85 °C
Lower temperature	-40 °C

Cable data

material housing	-
Insulation single lead	-
Single lead structure	-
Conductor resistance	-

Electrical values

Rated voltage	125 V
Rated impulse voltage	1500 V
Pollution degree	1
Overvoltage category	II
Material group	III
Rated current (40°C)	1 A
Volume resistivity	≤ 3 mΩ
EMV compliance	shieldable
Degree of protection	IP67
Mechanical operation	> 500 mating cycles

Material

Material of contact	CuSn (Bronze)
Contact plating	Au (Gold)
Material of contact body	PA (UL 94 V-0)
Material of housing	CuZn (Brass nickel-plated)

Contacts: 7, Female cable connector, 360° EMC safe, shieldable, cable outlet 3.5-5 mm

Product sheet

Subminiature connector



Product

**Contacts: 7, Female cable connector, 360°
EMC safe, cable outlet 3.5-5 mm**

Area

M9 IP67 Series 712

Pole

7

Article number

99 0422 10 07

Item description

