

Product	Contacts: 12, cable plug connector, black, injection-moulded cable	Area	Snap-in IP67 Series 720
Pole	12	Article number	79 9177 020 12

Illustration	Scale drawing	Contact Arrangement																								
		<table border="0" style="margin-left: auto; margin-right: 0;"> <tr><td>1</td><td>weiß/white</td></tr> <tr><td>2</td><td>braun/brown</td></tr> <tr><td>3</td><td>grün/green</td></tr> <tr><td>4</td><td>gelb/yellow</td></tr> <tr><td>5</td><td>grau/grey</td></tr> <tr><td>6</td><td>rosa/pink</td></tr> <tr><td>7</td><td>blau/blue</td></tr> <tr><td>8</td><td>rot/red</td></tr> <tr><td>9</td><td>schwarz/black</td></tr> <tr><td>10</td><td>violett/purple</td></tr> <tr><td>11</td><td>grau/rosa/grey/pink</td></tr> <tr><td>12</td><td>rot/blau/red/blue</td></tr> </table>	1	weiß/white	2	braun/brown	3	grün/green	4	gelb/yellow	5	grau/grey	6	rosa/pink	7	blau/blue	8	rot/red	9	schwarz/black	10	violett/purple	11	grau/rosa/grey/pink	12	rot/blau/red/blue
1	weiß/white																									
2	braun/brown																									
3	grün/green																									
4	gelb/yellow																									
5	grau/grey																									
6	rosa/pink																									
7	blau/blue																									
8	rot/red																									
9	schwarz/black																									
10	violett/purple																									
11	grau/rosa/grey/pink																									
12	rot/blau/red/blue																									

You can find the item description on the next page.

Technical data

Common values

Connector Design	Cable plug connector
Connector locking system	Snap
Termination	injection-moulded cable
Wire gauge (mm)	0.25 mm ²
Wire gauge (AWG)	24
Cable outlet	2.5 - 4 mm
Upper temperature	70 °C
Lower temperature	-40 °C

Cable data

material housing	PUR
Insulation single lead	PVC
Single lead structure	14 x 0.15
Cable sheath Ø	7
Conductor resistance	72Ω/Km (20°C)
Temperature range cable movable c from	-5
Temperature range cable movable c to	70
Temperature range cable fixed c from	-40
Temperature range cable fixed c to	70
Bending radius cable fixed	min. 40 mm
Bending radius cable movable	min. 70 mm

Electrical values

Rated voltage	60 V
Rated impulse voltage	800 V
Pollution degree	2
Overvoltage category	II
Material group	II
Rated current (40°C)	2 A
Volume resistivity	≤ 3 mΩ
EMV compliance	-
Degree of protection	IP67
Mechanical operation	> 500 mating cycles

Material

Material of contact	CuSn (Bronze)
Contact plating	Au (Gold)
Material of contact body	PA (UL 94 V-0)
Material of housing	PUR

Contacts: 12, cable plug connector, black, injection-moulded cable, cable length 2 m

Product	Contacts: 12, cable plug connector, black, injection-moulded cable	Area	Snap-in IP67 Series 720
Pole	12	Article number	79 9177 020 12

Item description

