

Product	Contacts: 5, Male angled connector overmoulded, stainless steel threaded ring	Area	M12-A Series 763
Pole	5	Article number	77 3727 0000 50005-0500

Illustration	Scale drawing	Contact Arrangement										
		<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 10px;">1</td> <td>braun/brown</td> </tr> <tr> <td style="padding-right: 10px;">2</td> <td>weiß/white</td> </tr> <tr> <td style="padding-right: 10px;">3</td> <td>blau/blue</td> </tr> <tr> <td style="padding-right: 10px;">4</td> <td>schwarz/black</td> </tr> <tr> <td style="padding-right: 10px;">5</td> <td>grau/grey</td> </tr> </table>	1	braun/brown	2	weiß/white	3	blau/blue	4	schwarz/black	5	grau/grey
1	braun/brown											
2	weiß/white											
3	blau/blue											
4	schwarz/black											
5	grau/grey											

Technical data

Common values

Connector Design	Male angled connector
Connector locking system	screw
Termination	crimp, injection-moulded cable
Wire gauge (mm)	0.25 mm ²
Wire gauge (AWG)	24
Upper temperature	85 °C
Lower temperature	-25 °C

Cable data

material housing	PUR
Insulation single lead	PVC
Single lead structure	32 x 0.1
Cable sheath Ø	5
Conductor resistance	55Ω/Km
Temperature range cable movable c from	-5
Temperature range cable movable c to	70
Temperature range cable fixed c from	-25
Temperature range cable fixed c to	70
Bending radius cable fixed	25 mm
Bending radius cable movable	50 mm

Electrical values

Rated voltage	125 V
Rated impulse voltage	1500 V
Pollution degree	3
Overvoltage category	II
Material group	II
Rated current (40°C)	4 A
Volume resistivity	≤ 3 mΩ
EMV compliance	nicht geschirmt
Degree of protection	IP68
Mechanical operation	> 100 mating cycles

Material

Material of contact	CuZn (Brass)
Contact plating	Au (Gold)
Material of contact body	PUR
Material of housing	PUR

Contacts: 5, Cable length 5 m, cable: 5 x 0.25 mm², PUR, male angled connector, overmoulded, stainless steel threaded ring