


Product **Contacts: 4, Female panel mount connector, front fastened, with single wires**
 Area **M16 IP67 Series 423/ 723/ 425**
 Article number **09 0112 782 04**

Illustration



Contact Arrangement



	X	Y
1	-3,32	-1,08
2	-2,05	2,83
3	2,05	2,83
4	3,32	-1,08

You can find the assembly instruction on the next page.

Technical data

General features

Connector Design female panel mount connector
 Connector locking system bolted
 Termination solder
 Wire gauge (mm) 0,75 mm²
 Wire gauge (AWG) 22
 Upper temperature 85 °C
 Lower temperature -30 °C

Cable data

Approval 1 UL

Electrical parameters

Rated voltage 300 V
 Rated impulse voltage 1500 V
 Pollution degree 1
 Overvoltage category I
 Material group II
 Rated current (40°C) 5 A
 Volume resistivity ≤ 5 mΩ
 EMV compliance shielded
 Degree of protection IP67
 Mechanical operation > 500 Mating cycles

Material

Material of contact CuSn (Bronze)
 Contact plating Ag (silver)
 Material of contact body PBT (UL 94 V-0)

Product	Contacts: 4, Female panel mount connector, front fastened, with single wires
Area	M16 IP67 Series 423/ 723/ 425
Article number	09 0112 782 04

Installation instructions / Mounting cutout

