

# Product sheet

## Miniature connector



Product	<b>Contacts: 2, Cable plug connector with solder eye, shieldable, cable outlet 6 – 8 mm</b>	Area	<b>M16 IP40 Series 581</b>
Pole	<b>2</b>	Article number	<b>99 2001 92 02</b>

Illustration	Scale drawing	Contact Arrangement									
		<table border="1" style="margin-left: 20px;"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>3,50</td> <td>0,00</td> </tr> <tr> <td>2</td> <td>-3,50</td> <td>0,00</td> </tr> </tbody> </table>		X	Y	1	3,50	0,00	2	-3,50	0,00
	X	Y									
1	3,50	0,00									
2	-3,50	0,00									

You can find the item description on the next page.

## Technical data

### Common values

Connector Design	Cable plug connector
Connector locking system	screw
Termination	Solder
Wire gauge (mm)	0.75 mm <sup>2</sup>
Wire gauge (AWG)	20
Cable outlet	6 - 7.8 mm
Upper temperature	85 °C
Lower temperature	-40 °C

### Electrical values

Rated voltage	250 V
Rated impulse voltage	1500 V
Pollution degree	1
Overvoltage category	I
Material group	III
Rated current (40°C)	7 A
Volume resistivity	≤ 3 mΩ
EMV compliance	shielded
Degree of protection	IP40
Mechanical operation	> 500 mating cycles

### Material

Material of contact	CuZn (Brass)
Contact plating	Au (Gold)
Material of contact body	PBT (UL 94 V-0)
Material of housing	CuZn (Brass nickel-plated)

Contacts: 2, Cable plug connector with solder eye, shieldable, cable outlet 6 – 8 mm, gold plated contacts

Product	<b>Contacts: 2, Cable plug connector with solder eye, shieldable, cable outlet 6 – 8 mm</b>	Area	<b>M16 IP40 Series 581</b>
Pole	<b>2</b>	Article number	<b>99 2001 92 02</b>

Item description

