

Product sheet

Output connector



Product	Contacts: 16, Male angled connector, central lock, PG 13.5, right-turning (the pin and socket insert counter-rotate in right and left turning models)	Area	M23 Power Series 623
Pole	16	Article number	99 4611 20 16

Illustration	Scale drawing	Contact Arrangement																																																			
		<table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> </tr> </thead> <tbody> <tr><td>1</td><td>1,70</td><td>5,50</td></tr> <tr><td>2</td><td>4,40</td><td>3,60</td></tr> <tr><td>3</td><td>5,70</td><td>0,70</td></tr> <tr><td>4</td><td>5,20</td><td>-2,50</td></tr> <tr><td>5</td><td>3,05</td><td>-4,80</td></tr> <tr><td>6</td><td>0,00</td><td>-5,70</td></tr> <tr><td>7</td><td>-3,05</td><td>-4,80</td></tr> <tr><td>8</td><td>-5,20</td><td>-2,50</td></tr> <tr><td>9</td><td>-5,70</td><td>0,70</td></tr> <tr><td>10</td><td>-4,40</td><td>3,60</td></tr> <tr><td>11</td><td>-1,70</td><td>5,50</td></tr> <tr><td>12</td><td>0,00</td><td>2,80</td></tr> <tr><td>13</td><td>2,55</td><td>1,10</td></tr> <tr><td>14</td><td>1,70</td><td>-2,00</td></tr> <tr><td>15</td><td>-1,70</td><td>-2,00</td></tr> <tr><td>16</td><td>-2,55</td><td>1,10</td></tr> </tbody> </table>		X	Y	1	1,70	5,50	2	4,40	3,60	3	5,70	0,70	4	5,20	-2,50	5	3,05	-4,80	6	0,00	-5,70	7	-3,05	-4,80	8	-5,20	-2,50	9	-5,70	0,70	10	-4,40	3,60	11	-1,70	5,50	12	0,00	2,80	13	2,55	1,10	14	1,70	-2,00	15	-1,70	-2,00	16	-2,55	1,10
	X	Y																																																			
1	1,70	5,50																																																			
2	4,40	3,60																																																			
3	5,70	0,70																																																			
4	5,20	-2,50																																																			
5	3,05	-4,80																																																			
6	0,00	-5,70																																																			
7	-3,05	-4,80																																																			
8	-5,20	-2,50																																																			
9	-5,70	0,70																																																			
10	-4,40	3,60																																																			
11	-1,70	5,50																																																			
12	0,00	2,80																																																			
13	2,55	1,10																																																			
14	1,70	-2,00																																																			
15	-1,70	-2,00																																																			
16	-2,55	1,10																																																			

Technical data

Common values

Connector Design	Male panel mount connector
Connector locking system	screw
Termination	Solder
Wire gauge (mm)	1.00 mm ²
Wire gauge (AWG)	18
Cable outlet	-
Upper temperature	125 °C
Lower temperature	-20 °C

Electrical values

Rated voltage	150 V
Rated impulse voltage	1500 V
Pollution degree	3
Overvoltage category	II
Material group	III
Rated current (40°C)	8 A
Volume resistivity	≤ 3 mΩ
EMV compliance	not shielded
Degree of protection	IP67
Mechanical operation	> 50 mating cycles

Material

Material of contact	CuZn (Brass)
Contact plating	Au (Gold)
Material of contact body	PBT/PA66
Material of housing	Nickel-plated zinc die casting

Contacts: 16, Male panel mount connector, central lock, PG 13.5, right-turning