

Product **connecting cable, overmoulded, F&B, stainless steel,PVC grey**
 Area **M12-A Series 763 FOOD & BEVERAGE**
 Article number **77 3734 3727 20912-0200**

Illustration	Scale drawing	Contact Arrangement																								
		<table style="margin-left: auto; margin-right: auto;"> <tr><td>1</td><td>braun/brown</td></tr> <tr><td>2</td><td>blau/blue</td></tr> <tr><td>3</td><td>weiß/white</td></tr> <tr><td>4</td><td>grün/green</td></tr> <tr><td>5</td><td>rosa/pink</td></tr> <tr><td>6</td><td>gelb/yellow</td></tr> <tr><td>7</td><td>schwarz/black</td></tr> <tr><td>8</td><td>grau/grey</td></tr> <tr><td>9</td><td>rot/red</td></tr> <tr><td>10</td><td>violett/purple</td></tr> <tr><td>11</td><td>grau/rosa/grey/pink</td></tr> <tr><td>12</td><td>rot/blau/red/blue</td></tr> </table>	1	braun/brown	2	blau/blue	3	weiß/white	4	grün/green	5	rosa/pink	6	gelb/yellow	7	schwarz/black	8	grau/grey	9	rot/red	10	violett/purple	11	grau/rosa/grey/pink	12	rot/blau/red/blue
1	braun/brown																									
2	blau/blue																									
3	weiß/white																									
4	grün/green																									
5	rosa/pink																									
6	gelb/yellow																									
7	schwarz/black																									
8	grau/grey																									
9	rot/red																									
10	violett/purple																									
11	grau/rosa/grey/pink																									
12	rot/blau/red/blue																									

Technical data

<h3 style="color: #0070C0;">General features</h3> <table border="0" style="width: 100%;"> <tr> <td style="width: 50%;">Connector Design</td> <td>Cable Connector</td> </tr> <tr> <td>Connector locking system</td> <td>screw</td> </tr> <tr> <td>Termination</td> <td>crimp, overmoulded on cable</td> </tr> <tr> <td>Wire gauge (mm)</td> <td>0,25</td> </tr> <tr> <td>Wire gauge (AWG)</td> <td>24</td> </tr> <tr> <td>Upper temperature</td> <td>105 °C</td> </tr> <tr> <td>Lower temperature</td> <td>-40 °C</td> </tr> </table>		Connector Design	Cable Connector	Connector locking system	screw	Termination	crimp, overmoulded on cable	Wire gauge (mm)	0,25	Wire gauge (AWG)	24	Upper temperature	105 °C	Lower temperature	-40 °C	<h3 style="color: #0070C0;">Electrical parameters</h3> <table border="0" style="width: 100%;"> <tr> <td>Rated voltage</td> <td>30 V</td> </tr> <tr> <td>Rated impulse voltage</td> <td>800 V</td> </tr> <tr> <td>Pollution degree</td> <td>3</td> </tr> <tr> <td>Overvoltage category</td> <td>II</td> </tr> <tr> <td>Material group</td> <td>II</td> </tr> <tr> <td>Rated current (40°C)</td> <td>1,5 A</td> </tr> <tr> <td>Volume resistivity</td> <td>$\leq 3\text{ m}\Omega$</td> </tr> <tr> <td>EMV compliance</td> <td>not shielded</td> </tr> <tr> <td>Degree of protection</td> <td>IP69K</td> </tr> <tr> <td>Mechanical operation</td> <td>> 100 Mating cycles</td> </tr> </table>	Rated voltage	30 V	Rated impulse voltage	800 V	Pollution degree	3	Overvoltage category	II	Material group	II	Rated current (40°C)	1,5 A	Volume resistivity	$\leq 3\text{ m}\Omega$	EMV compliance	not shielded	Degree of protection	IP69K	Mechanical operation	> 100 Mating cycles
Connector Design	Cable Connector																																			
Connector locking system	screw																																			
Termination	crimp, overmoulded on cable																																			
Wire gauge (mm)	0,25																																			
Wire gauge (AWG)	24																																			
Upper temperature	105 °C																																			
Lower temperature	-40 °C																																			
Rated voltage	30 V																																			
Rated impulse voltage	800 V																																			
Pollution degree	3																																			
Overvoltage category	II																																			
Material group	II																																			
Rated current (40°C)	1,5 A																																			
Volume resistivity	$\leq 3\text{ m}\Omega$																																			
EMV compliance	not shielded																																			
Degree of protection	IP69K																																			
Mechanical operation	> 100 Mating cycles																																			
<h3 style="color: #0070C0;">Cable data</h3> <table border="0" style="width: 100%;"> <tr> <td style="width: 50%;">material housing</td> <td>PVC</td> </tr> <tr> <td>Insulation single lead</td> <td>PVC</td> </tr> <tr> <td>Single lead structure</td> <td>32 x 0,1</td> </tr> <tr> <td>Cable sheath Ø</td> <td>6,6</td> </tr> <tr> <td>Conductor resistance</td> <td>75 Ω/Km (20°C)</td> </tr> <tr> <td>Temperature range cable movable °C from</td> <td>-5</td> </tr> <tr> <td>Temperature range cable movable °C to</td> <td>105</td> </tr> <tr> <td>Temperature range cable fixed °C from</td> <td>-40</td> </tr> <tr> <td>Temperature range cable fixed °C to</td> <td>105</td> </tr> <tr> <td>Bending radius cable fixed</td> <td>min. 5 x D</td> </tr> <tr> <td>Bending radius cable movable</td> <td>min. 10 x D</td> </tr> <tr> <td>Approval 1</td> <td>UL listed</td> </tr> <tr> <td>Approval 2</td> <td>Ecolab</td> </tr> </table>		material housing	PVC	Insulation single lead	PVC	Single lead structure	32 x 0,1	Cable sheath Ø	6,6	Conductor resistance	75 Ω /Km (20°C)	Temperature range cable movable °C from	-5	Temperature range cable movable °C to	105	Temperature range cable fixed °C from	-40	Temperature range cable fixed °C to	105	Bending radius cable fixed	min. 5 x D	Bending radius cable movable	min. 10 x D	Approval 1	UL listed	Approval 2	Ecolab	<h3 style="color: #0070C0;">Material</h3> <table border="0" style="width: 100%;"> <tr> <td style="width: 50%;">Material of contact</td> <td>CuSn (Bronze)</td> </tr> <tr> <td>Contact plating</td> <td>Au (gold)</td> </tr> <tr> <td>Material of contact body</td> <td>PP</td> </tr> <tr> <td>Material of housing</td> <td>PP</td> </tr> </table>	Material of contact	CuSn (Bronze)	Contact plating	Au (gold)	Material of contact body	PP	Material of housing	PP
material housing	PVC																																			
Insulation single lead	PVC																																			
Single lead structure	32 x 0,1																																			
Cable sheath Ø	6,6																																			
Conductor resistance	75 Ω /Km (20°C)																																			
Temperature range cable movable °C from	-5																																			
Temperature range cable movable °C to	105																																			
Temperature range cable fixed °C from	-40																																			
Temperature range cable fixed °C to	105																																			
Bending radius cable fixed	min. 5 x D																																			
Bending radius cable movable	min. 10 x D																																			
Approval 1	UL listed																																			
Approval 2	Ecolab																																			
Material of contact	CuSn (Bronze)																																			
Contact plating	Au (gold)																																			
Material of contact body	PP																																			
Material of housing	PP																																			