


Product **Contacts: 8 DIN, Male panel mount connector, front fastened, with single wires**  
 Area **M16 IP40 Series 581/ 680/ 682**  
 Article number **09 0473 782 08**

### Illustration



### Contact Arrangement



	X	Y
1	3,50	0,00
2	0,00	3,50
3	-3,50	0,00
4	2,47	2,47
5	-2,47	2,47
6	2,47	-2,47
7	-2,47	-2,47
8	0,00	-0,70

**You can find the assembly instruction on the next page.**

## Technical data

### General features

Connector Design male panel mount connector  
 Connector locking system bolted  
 Termination Strands  
 Wire gauge (mm) 0,75 mm<sup>2</sup>  
 Wire gauge (AWG) 22  
 Upper temperature 85 °C  
 Lower temperature -30 °C

### Electrical parameters

Rated voltage 100 V  
 Rated impulse voltage 1200 V  
 Pollution degree 1  
 Overvoltage category I  
 Material group II  
 Rated current (40°C) 5 A  
 Volume resistivity ≤ 5 mΩ  
 EMV compliance shielded  
 Degree of protection IP40  
 Mechanical operation > 500 Mating cycles

### Material

Material of contact CuSn (Bronze)  
 Contact plating Ag (silver)  
 Material of contact body PBT (UL 94 V-0)

Product	Contacts: 8 DIN, Male panel mount connector, front fastened, with single wires
Area	M16 IP40 Series 581/ 680/ 682
Article number	09 0473 782 08

### Installation instructions / Mounting cutout

