

Product **connecting cable, overmoulded, F&B, stainless steel,PVC grey**
 Area **M12-A Series 763 FOOD & BEVERAGE**
 Article number **77 3734 3729 20912-0200**

Illustration	Scale drawing	Contact Arrangement																								
		<table border="0" style="margin-left: auto; margin-right: auto;"> <tr><td>1</td><td>braun/brown</td></tr> <tr><td>2</td><td>blau/blue</td></tr> <tr><td>3</td><td>weiß/white</td></tr> <tr><td>4</td><td>grün/green</td></tr> <tr><td>5</td><td>rosa/pink</td></tr> <tr><td>6</td><td>gelb/yellow</td></tr> <tr><td>7</td><td>schwarz/black</td></tr> <tr><td>8</td><td>grau/grey</td></tr> <tr><td>9</td><td>rot/red</td></tr> <tr><td>10</td><td>violett/purple</td></tr> <tr><td>11</td><td>grau/rosa/grey/pink</td></tr> <tr><td>12</td><td>rot/blau/red/blue</td></tr> </table>	1	braun/brown	2	blau/blue	3	weiß/white	4	grün/green	5	rosa/pink	6	gelb/yellow	7	schwarz/black	8	grau/grey	9	rot/red	10	violett/purple	11	grau/rosa/grey/pink	12	rot/blau/red/blue
1	braun/brown																									
2	blau/blue																									
3	weiß/white																									
4	grün/green																									
5	rosa/pink																									
6	gelb/yellow																									
7	schwarz/black																									
8	grau/grey																									
9	rot/red																									
10	violett/purple																									
11	grau/rosa/grey/pink																									
12	rot/blau/red/blue																									

Technical data

<h3 style="color: #0070C0;">General features</h3> <table border="0" style="width: 100%;"> <tr><td>Connector Design</td><td>Cable Connector</td></tr> <tr><td>Connector locking system</td><td>screw</td></tr> <tr><td>Termination</td><td>crimp, overmoulded on cable</td></tr> <tr><td>Wire gauge (mm)</td><td>0,25</td></tr> <tr><td>Wire gauge (AWG)</td><td>24</td></tr> <tr><td>Upper temperature</td><td>105 °C</td></tr> <tr><td>Lower temperature</td><td>-40 °C</td></tr> </table>		Connector Design	Cable Connector	Connector locking system	screw	Termination	crimp, overmoulded on cable	Wire gauge (mm)	0,25	Wire gauge (AWG)	24	Upper temperature	105 °C	Lower temperature	-40 °C	<h3 style="color: #0070C0;">Electrical parameters</h3> <table border="0" style="width: 100%;"> <tr><td>Rated voltage</td><td>30 V</td></tr> <tr><td>Rated impulse voltage</td><td>800 V</td></tr> <tr><td>Pollution degree</td><td>3</td></tr> <tr><td>Overvoltage category</td><td>II</td></tr> <tr><td>Material group</td><td>II</td></tr> <tr><td>Rated current (40°C)</td><td>1,5 A</td></tr> <tr><td>Volume resistivity</td><td>≤ 3 mΩ</td></tr> <tr><td>EMV compliance</td><td>not shielded</td></tr> <tr><td>Degree of protection</td><td>IP69K</td></tr> <tr><td>Mechanical operation</td><td>> 100 Mating cycles</td></tr> </table>		Rated voltage	30 V	Rated impulse voltage	800 V	Pollution degree	3	Overvoltage category	II	Material group	II	Rated current (40°C)	1,5 A	Volume resistivity	≤ 3 mΩ	EMV compliance	not shielded	Degree of protection	IP69K	Mechanical operation	> 100 Mating cycles
Connector Design	Cable Connector																																				
Connector locking system	screw																																				
Termination	crimp, overmoulded on cable																																				
Wire gauge (mm)	0,25																																				
Wire gauge (AWG)	24																																				
Upper temperature	105 °C																																				
Lower temperature	-40 °C																																				
Rated voltage	30 V																																				
Rated impulse voltage	800 V																																				
Pollution degree	3																																				
Overvoltage category	II																																				
Material group	II																																				
Rated current (40°C)	1,5 A																																				
Volume resistivity	≤ 3 mΩ																																				
EMV compliance	not shielded																																				
Degree of protection	IP69K																																				
Mechanical operation	> 100 Mating cycles																																				
<h3 style="color: #0070C0;">Cable data</h3> <table border="0" style="width: 100%;"> <tr><td>material housing</td><td>PVC</td></tr> <tr><td>Insulation single lead</td><td>PVC</td></tr> <tr><td>Single lead structure</td><td>32 x 0,1</td></tr> <tr><td>Cable sheath Ø</td><td>6,6</td></tr> <tr><td>Conductor resistance</td><td>75 Ω/Km (20°C)</td></tr> <tr><td>Temperature range cable movable °C from</td><td>-5</td></tr> <tr><td>Temperature range cable movable °C to</td><td>105</td></tr> <tr><td>Temperature range cable fixed °C from</td><td>-40</td></tr> <tr><td>Temperature range cable fixed °C to</td><td>105</td></tr> <tr><td>Bending radius cable fixed</td><td>min. 5 x D</td></tr> <tr><td>Bending radius cable movable</td><td>min. 10 x D</td></tr> <tr><td>Approval 1</td><td>UL listed</td></tr> <tr><td>Approval 2</td><td>Ecolab</td></tr> </table>		material housing	PVC	Insulation single lead	PVC	Single lead structure	32 x 0,1	Cable sheath Ø	6,6	Conductor resistance	75 Ω/Km (20°C)	Temperature range cable movable °C from	-5	Temperature range cable movable °C to	105	Temperature range cable fixed °C from	-40	Temperature range cable fixed °C to	105	Bending radius cable fixed	min. 5 x D	Bending radius cable movable	min. 10 x D	Approval 1	UL listed	Approval 2	Ecolab	<h3 style="color: #0070C0;">Material</h3> <table border="0" style="width: 100%;"> <tr><td>Material of contact</td><td>CuSn (Bronze)</td></tr> <tr><td>Contact plating</td><td>Au (gold)</td></tr> <tr><td>Material of contact body</td><td>PP</td></tr> <tr><td>Material of housing</td><td>PP</td></tr> </table>		Material of contact	CuSn (Bronze)	Contact plating	Au (gold)	Material of contact body	PP	Material of housing	PP
material housing	PVC																																				
Insulation single lead	PVC																																				
Single lead structure	32 x 0,1																																				
Cable sheath Ø	6,6																																				
Conductor resistance	75 Ω/Km (20°C)																																				
Temperature range cable movable °C from	-5																																				
Temperature range cable movable °C to	105																																				
Temperature range cable fixed °C from	-40																																				
Temperature range cable fixed °C to	105																																				
Bending radius cable fixed	min. 5 x D																																				
Bending radius cable movable	min. 10 x D																																				
Approval 1	UL listed																																				
Approval 2	Ecolab																																				
Material of contact	CuSn (Bronze)																																				
Contact plating	Au (gold)																																				
Material of contact body	PP																																				
Material of housing	PP																																				