

Product **connecting cable, overmoulded, F&B, stainless steel,PVC grey**
 Area **M12-A Series 763 FOOD & BEVERAGE**
 Article number **77 3730 3727 20908-0200**

Illustration	Scale drawing	Contact Arrangement																		
		<table border="1"> <thead> <tr> <th>geschirmt/ shielded</th> <th>nicht geschirmt/ not shielded</th> </tr> </thead> <tbody> <tr><td>1 weiß/white</td><td>1 weiß/white</td></tr> <tr><td>2 braun/brown</td><td>2 braun/brown</td></tr> <tr><td>3 grün/green</td><td>3 grün/green</td></tr> <tr><td>4 gelb/yellow</td><td>4 gelb/yellow</td></tr> <tr><td>5 grau/grey</td><td>5 grau/grey</td></tr> <tr><td>6 rosa/pink</td><td>6 rosa/pink</td></tr> <tr><td>7 blau/blue</td><td>7 blau/blue</td></tr> <tr><td>8 rot/red</td><td>8 Schirm/shield</td></tr> </tbody> </table> <p>Gehäuse-Schirm/ Housing-shield</p>	geschirmt/ shielded	nicht geschirmt/ not shielded	1 weiß/white	1 weiß/white	2 braun/brown	2 braun/brown	3 grün/green	3 grün/green	4 gelb/yellow	4 gelb/yellow	5 grau/grey	5 grau/grey	6 rosa/pink	6 rosa/pink	7 blau/blue	7 blau/blue	8 rot/red	8 Schirm/shield
geschirmt/ shielded	nicht geschirmt/ not shielded																			
1 weiß/white	1 weiß/white																			
2 braun/brown	2 braun/brown																			
3 grün/green	3 grün/green																			
4 gelb/yellow	4 gelb/yellow																			
5 grau/grey	5 grau/grey																			
6 rosa/pink	6 rosa/pink																			
7 blau/blue	7 blau/blue																			
8 rot/red	8 Schirm/shield																			

Technical data

General features

Connector Design	Cable Connector
Connector locking system	screw
Termination	crimp, overmoulded on cable
Wire gauge (mm)	0,25
Wire gauge (AWG)	24
Upper temperature	105 °C
Lower temperature	-40 °C

Cable data

material housing	PVC
Insulation single lead	PVC
Single lead structure	32 x 0,1
Cable sheath Ø	6
Conductor resistance	<79 Ω/Km (20°C)
Temperature range cable movable °C from	-5
Temperature range cable movable °C to	105
Temperature range cable fixed °C from	-40
Temperature range cable fixed °C to	105
Bending radius cable fixed	min. 5 x D
Bending radius cable movable	min. 10 x D
Approval 1	UL listed
Approval 2	Ecolab

Electrical parameters

Rated voltage	30 V
Rated impulse voltage	800 V
Pollution degree	3
Overvoltage category	II
Material group	II
Rated current (40°C)	2 A
Volume resistivity	≤ 3 mΩ
EMV compliance	not shielded
Degree of protection	IP69K
Mechanical operation	> 100 Mating cycles

Material

Material of contact	CuSn (Bronze)
Contact plating	Au (gold)
Material of contact body	PP
Material of housing	PP