

Product sheet

Output connector



Product	Contacts: 6, Coupling socket, shieldable, right-turning (the pin and socket insert counter-rotate in right and left turning models)	Area	M23 Power Series 623
Pole	6	Article number	99 4650 00 06

Illustration	Scale drawing	Contact Arrangement																					
		<table border="1" style="margin-left: 20px;"> <thead> <tr> <th></th> <th>X</th> <th>Y</th> </tr> </thead> <tbody> <tr><td>1</td><td>-4,13</td><td>2,38</td></tr> <tr><td>2</td><td>-4,13</td><td>-2,38</td></tr> <tr><td>3</td><td>0,00</td><td>-4,75</td></tr> <tr><td>4</td><td>4,13</td><td>-2,38</td></tr> <tr><td>5</td><td>4,13</td><td>2,38</td></tr> <tr><td>6</td><td>0,00</td><td>0,00</td></tr> </tbody> </table>		X	Y	1	-4,13	2,38	2	-4,13	-2,38	3	0,00	-4,75	4	4,13	-2,38	5	4,13	2,38	6	0,00	0,00
	X	Y																					
1	-4,13	2,38																					
2	-4,13	-2,38																					
3	0,00	-4,75																					
4	4,13	-2,38																					
5	4,13	2,38																					
6	0,00	0,00																					

Technical data

Common values

Connector Design	Female cable connector
Connector locking system	screw
Termination	Solder
Wire gauge (mm)	2.50 mm ²
Wire gauge (AWG)	14
Cable outlet	6 - 10 mm
Upper temperature	125 °C
Lower temperature	-20 °C

Electrical values

Rated voltage	300 V
Rated impulse voltage	2500 V
Pollution degree	3
Overvoltage category	II
Material group	III
Rated current (40°C)	20 A
Volume resistivity	≤ 3 mΩ
EMV compliance	shielded
Degree of protection	IP67
Mechanical operation	> 50 mating cycles

Material

Material of contact	CuSn (Bronze)
Contact plating	Au (Gold)
Material of contact body	PBT/PA66
Material of housing	CuZn (Brass nickel-plated)

Contacts: 6, Coupling socket, shieldable, right-turning