


Product **Cable length: 2 m, Contacts: 2, Female cable connector, PROFIBUS, with UL approval**
 Area **M12-B Series 766**
 Article number **77 4330 0000 60702 0200**

Illustration



Scale drawing



- 1 n. C.
- 2 grün/green
- 3 n. C.
- 4 rot/red
- 5 n. C.
- Schirm Schirmhülse
- shield shielding sleeve

Technical data

Common values

Connector Design	Female cable connector
Connector locking system	screw
Termination	crimp, injection-moulded cable
Wire gauge (mm)	0.25 mm ²
Wire gauge (AWG)	22
Upper temperature	85 °C
Lower temperature	-25 °C

Electrical values

Rated voltage	250 V
Rated impulse voltage	2500 V
Pollution degree	3
Overvoltage category	II
Material group	II
Rated current (40°C)	4 A
Volume resistivity	≤ 3 mΩ
Degree of protection	IP67
Mechanical operation	> 500 mating cycles

Cable data

material housing	PUR
Insulation single lead	PE foam
Single lead structure	19 x 0.127 mm
Cable sheath Ø	7.8
Approval	UL style: 20236

Material

Material of contact	CuSn (Bronze)
Contact plating	Au (Gold)
Material of contact body	PUR
Material of housing	PUR