


Product **Contacts: 6 DIN, Female panel mount connector, front fastened, with single wires**
 Area **M16 IP40 Series 581/ 680/ 682**
 Article number **09 0324 782 06**

Illustration



Contact Arrangement



	X	Y
1	-3,03	-1,75
2	-3,03	1,75
3	0,00	3,50
4	3,03	1,75
5	3,03	-1,75
6	0,00	0,00

You can find the assembly instruction on the next page.

Technical data

General features

Connector Design female panel mount connector
 Connector locking system bolted
 Termination Strands
 Wire gauge (mm) 0,75 mm²
 Wire gauge (AWG) 22
 Upper temperature 85 °C
 Lower temperature -30 °C

Electrical parameters

Rated voltage 300 V
 Rated impulse voltage 1500 V
 Pollution degree 1
 Overvoltage category I
 Material group II
 Rated current (40°C) 5 A
 Volume resistivity ≤ 5 mΩ
 EMV compliance shielded
 Degree of protection IP40
 Mechanical operation > 500 Mating cycles

Material

Material of contact CuSn (Bronze)
 Contact plating Ag (silver)
 Material of contact body PBT (UL 94 V-0)

Product	Contacts: 6 DIN, Female panel mount connector, front fastened, with single wires
Area	M16 IP40 Series 581/ 680/ 682
Article number	09 0324 782 06

Installation instructions / Mounting cutout

