

Product	Contacts: 5, Female cable connector, CAN bus, with UL approval	Area	M12-A Series 763
Pole	5	Article number	77 2530 0000 50705-0500

Illustration	Scale drawing	Contact Arrangement
		<ul style="list-style-type: none"> 1 Schirm/shield 2 rot/red (AWG22) 3 schwarz/black (AWG22) 4 weiß/white (AWG24) 5 blau/blue (AWG24)

Technical data

Common values

Connector Design	Female cable connector
Connector locking system	screw
Termination	crimp, injection-moulded cable
Wire gauge (mm)	1 x 2 x AWG 22/ 1 x 2 x AWG 24
Wire gauge (AWG)	1 x 2 x AWG 22/ 1 x 2 x AWG 24
Upper temperature	85 °C
Lower temperature	-25 °C

Cable data

material housing	PUR
Insulation single lead	Polyolefin
Single lead structure	19x0.16/19x0.13
Cable sheath Ø	7.2
Approval	UL style: UL 1581, UL 444

Electrical values

Rated voltage	60 V
Rated impulse voltage	1500 V
Pollution degree	3
Overvoltage category	II
Material group	II
Rated current (40°C)	4 A
Volume resistivity	≤ 3 mΩ
EMV compliance	shielded
Degree of protection	IP67
Mechanical operation	> 100 mating cycles

Material

Material of contact	CuSn (Bronze)
Contact plating	Au (Gold)
Material of contact body	PUR
Material of housing	PUR

Contacts: 5, Cable length 5 m, female cable connector, CAN bus, with UL approval