

Product	Contacts: 3, female cable connector, black, injection-moulded cable	Area	Snap-in IP67 Series 720
Pole	3	Article number	79 9150 020 03

Illustration	Scale drawing	Contact Arrangement
		<div style="margin-left: 20px;"> <p>1 weiß/white 2 braun/brown 3 grün/green</p> </div>

You can find the item description on the next page.

Technical data

Common values

Connector Design	Female cable connector
Connector locking system	Snap
Termination	injection-moulded cable
Wire gauge (mm)	0.75 mm ²
Wire gauge (AWG)	20
Cable outlet	2.5 - 4 mm
Upper temperature	70 °C
Lower temperature	-40 °C

Cable data

material housing	PUR
Insulation single lead	PVC
Single lead structure	24 x 0.2
Cable sheath Ø	6.9
Conductor resistance	28Ω/Km (20°C)
Temperature range cable movable c from	-5
Temperature range cable movable c to	70
Temperature range cable fixed c from	-40
Temperature range cable fixed c to	70
Bending radius cable fixed	min. 40 mm
Bending radius cable movable	min. 70 mm

Electrical values

Rated voltage	250 V
Rated impulse voltage	2500 V
Pollution degree	2
Overvoltage category	II
Material group	II
Rated current (40°C)	7 A
Volume resistivity	≤ 3 mΩ
EMV compliance	-
Degree of protection	IP67
Mechanical operation	> 500 mating cycles

Material

Material of contact	CuSn (Bronze)
Contact plating	Au (Gold)
Material of contact body	PA (UL 94 V-0)
Material of housing	PUR

Contacts: 3, female cable connector, black, injection-moulded cable, cable length 2 m

Product	Contacts: 3, female cable connector, black, injection-moulded cable	Area	Snap-in IP67 Series 720
Pole	3	Article number	79 91 50 020 03

Item description

