


Product	<b>Contacts: 3, Female cable connector overmoulded, stainless steel threaded ring</b>	Area	<b>M12-A Series 763</b>
Pole	<b>3</b>	Article number	<b>77 3730 0000 50004-0500</b>


### Illustration



### Scale drawing




### Contact Arrangement



- 1 braun/brown
- 3 blau/blue
- 4 schwarz/black

### Attenuation characteristic



## Technical data

### Common values

Connector Design	Female cable connector
Connector locking system	screw
Termination	crimp, injection-moulded cable
Wire gauge (mm)	0.34 mm <sup>2</sup>
Wire gauge (AWG)	22
Upper temperature	85 °C
Lower temperature	-25 °C

### Electrical values

Rated voltage	250 V
Rated impulse voltage	2500 V
Pollution degree	3
Overvoltage category	II
Material group	II
Rated current (40°C)	4 A
Volume resistivity	≤ 3 mΩ
EMV compliance	not shielded
Degree of protection	IP68
Mechanical operation	> 100 mating cycles

### Material

Material of contact	CuSn (Bronze)
Contact plating	Au (Gold)
Material of contact body	PUR
Material of housing	PUR

Contacts: 4, Cable length 5 m, cable: 4 x 0.34 mm<sup>2</sup>, PUR, female cable connector, overmoulded, stainless steel threaded ring

Product	<b>Contacts: 3, Female cable connector overmoulded, stainless steel threaded ring</b>	Area	<b>M12-A Series 763</b>
Pole	<b>3</b>	Article number	<b>77 3730 0000 50004-0500</b>

## Technical data

### Cable data

material housing	PUR
Insulation single lead	PVC
Single lead structure	42 x 0.1
Cable sheath Ø	5
Conductor resistance	55Ω/Km
Temperature range cable movable c from	-5
Temperature range cable movable c to	70
Temperature range cable fixed c from	-25
Temperature range cable fixed c to	70
Bending radius cable fixed	25 mm
Bending radius cable movable	50 mm