

Product	<b>Contacts: 5, Cable plug connector</b>	Area	<b>M16 IP67 Series 425</b>
Pole	<b>5</b>	Article number	<b>79 6013 20 05</b>

Illustration	Scale drawing	Contact Arrangement										
		<table style="margin-left: auto; margin-right: 0;"> <tr><td>1</td><td>weiß</td></tr> <tr><td>2</td><td>braun</td></tr> <tr><td>3</td><td>blau</td></tr> <tr><td>4</td><td>schwarz</td></tr> <tr><td>5</td><td>grau</td></tr> </table>	1	weiß	2	braun	3	blau	4	schwarz	5	grau
1	weiß											
2	braun											
3	blau											
4	schwarz											
5	grau											

## Technical data

### Common values

Connector Design	Cable plug connector
Connector locking system	screw
Termination	solder, injection-moulded cable
Wire gauge (mm)	0.25 mm <sup>2</sup>
Wire gauge (AWG)	24
Cable outlet	-
Upper temperature	70 °C
Lower temperature	-25 °C

### Cable data

material housing	PUR
Insulation single lead	PVC
Single lead structure	32x0.1 mm
Cable sheath Ø	5
Bending radius cable fixed	50 mm
Bending radius cable movable	75 mm
Cable diameter	5

### Electrical values

Rated voltage	250 V
Rated impulse voltage	1500 V
Pollution degree	1
Overvoltage category	I
Material group	III
Rated current (40°C)	3 A
Volume resistivity	≤ 3 mΩ
EMV compliance	not shielded
Degree of protection	IP67
Mechanical operation	> 500 mating cycles

### Material

Material of contact	CuZn (Brass)
Contact plating	Au (Gold)
Material of contact body	PBT (UL 94 V-0)
Material of housing	PUR

Contacts: 5, Cable: 5 x 0.25 mm<sup>2</sup>, cable plug connector