


Product	<b>Polzahl: 4, Winkeldose umspritzt, Edelstahlgewinding</b>	Area	<b>M12-A Series 763</b>
Pole	<b>4</b>	Article number	<b>77 3734 0000 50004-0200</b>

### Illustration



### Scale drawing



## Technical data

### Common values

Connector locking system	screw
Termination	crimp, injection-moulded cable
Wire gauge (mm)	0.34 mm <sup>2</sup>
Wire gauge (AWG)	22
Upper temperature	85 °C
Lower temperature	-25 °C

### Cable data

material housing	PUR
Insulation single lead	PVC
Single lead structure	42 x 0.1
Cable sheath Ø	5
Conductor resistance	55Ω/Km
Temperature range cable movable c from	-5
Temperature range cable movable c to	70
Temperature range cable fixed c from	-25
Temperature range cable fixed c to	70
Bending radius cable fixed	25 mm
Bending radius cable movable	50 mm

### Electrical values

Pollution degree	3
Overvoltage category	II
Material group	II
Rated current (40°C)	4 A
Volume resistivity	≤ 3 mΩ
EMV compliance	nicht geschirmt
Degree of protection	IP68
Mechanical operation	> 100 mating cycles

### Material

Material of contact	CuSn (Bronze)
Contact plating	Au (Gold)
Material of contact body	PUR
Material of housing	PUR

Polzahl: 4, Kabellänge 2 m, Kabel: 4 x 0,34 mm<sup>2</sup>, PUR, Winkeldose umspritzt, Edelstahlgewinding